

COUNCIL REGULATION (EU) 2020/2231**of 18 December 2020****amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient and uninterrupted supply of certain agricultural and industrial products which are not produced in the Union and thereby avoid any disturbances in the market for those products, Common Customs Tariff duties of the type referred to in Article 56(2)(c) of Regulation (EU) No 952/2013 of the European Parliament and of the Council⁽¹⁾ ('CCT duties') on those products have been suspended by Council Regulation (EU) No 1387/2013⁽²⁾. Those products can be imported into the Union at reduced or zero duty rates.
- (2) The Union production of certain products that are not listed in the Annex to Regulation (EU) No 1387/2013 is inadequate or non-existent. It is therefore in the interest of the Union to grant a complete suspension of the CCT duties on those products.
- (3) With a view to promoting integrated battery production in the Union in accordance with the communication from the Commission of 17 May 2018 entitled 'Europe on the Move – Sustainable Mobility for Europe: safe, connected, and clean', a partial suspension of the CCT duties should be granted in respect of certain products that are not listed in the Annex to Regulation (EU) No 1387/2013. In addition, only a partial suspension of the CCT duties should be granted in respect of certain products that are currently subject to complete suspensions. The date for the mandatory review of those suspensions should be 31 December 2021, in order for that review to take into account the evolution of the battery sector in the Union.
- (4) It is necessary to amend the product description, classification and end-use requirement for certain CCT duty suspensions listed in the Annex to Regulation (EU) No 1387/2013 in order to take into account technical product developments and economic trends in the market.
- (5) A review has been undertaken of certain CCT duty suspensions listed in the Annex to Regulation (EU) No 1387/2013. New dates should therefore be set for their next mandatory review.
- (6) It is no longer in the interest of the Union to maintain the suspension of CCT duties for certain products listed in the Annex to Regulation (EU) No 1387/2013. The suspensions for those products should therefore be deleted. Moreover, according to the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, for practical reasons requests for tariff suspensions or quotas where the amount of uncollected customs duty is estimated to be less than EUR 15 000 per year cannot be taken into consideration. The suspensions for products which do not reach that threshold, as indicated by the mandatory review, should therefore be deleted from the Annex to Regulation (EU) No 1387/2013.
- (7) Regulation (EU) No 1387/2013 should therefore be amended accordingly.

⁽¹⁾ Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).

⁽²⁾ Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

- (8) In order to avoid any interruption in the application of the autonomous tariff suspension scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the tariff suspensions for the products concerned should apply from 1 January 2021. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EU) No 1387/2013 is amended in accordance with the Annex to this Regulation.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2021.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 18 December 2020.

For the Council
The President
M. ROTH

ANNEX

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

(1) the entries with the following serial numbers are deleted:

0.3338, 0.3662, 0.4675, 0.4795, 0.4856, 0.4891, 0.4902, 0.4903, 0.4905, 0.4908, 0.4911, 0.4920, 0.4926, 0.4935, 0.4939, 0.4943, 0.4973, 0.4995, 0.5012, 0.5022, 0.5039, 0.5043, 0.5052, 0.5053, 0.5067, 0.5092, 0.5103, 0.5123, 0.5125, 0.5126, 0.5311, 0.5498, 0.5953, 0.6036, 0.6068, 0.6087, 0.6450, 0.6527, 0.6591, 0.6592, 0.6595, 0.6596, 0.6597, 0.6606, 0.6607, 0.6608, 0.6610, 0.6615, 0.6616, 0.6619, 0.6626, 0.6636, 0.6639, 0.6651, 0.6653, 0.6665, 0.6676, 0.6694, 0.6697, 0.6704, 0.6705, 0.6715, 0.6724, 0.6727, 0.6731, 0.6733, 0.6735, 0.6743, 0.6744, 0.6755, 0.6756, 0.6758, 0.6760, 0.6768, 0.6775, 0.6776, 0.6778, 0.6780, 0.6785, 0.6786, 0.6787, 0.6788, 0.6795, 0.6798, 0.6803, 0.6807, 0.6811, 0.6832, 0.6833, 0.6834, 0.6838, 0.6841, 0.6883, 0.6890, 0.6895, 0.6900, 0.6902, 0.6909, 0.6914, 0.6916, 0.6918, 0.6928, 0.6941, 0.6942, 0.6943, 0.6944, 0.6953, 0.6954, 0.7040, 0.7222, 0.7293, 0.7558, 0.7560, 0.7697, 0.7715 and 0.7855;

(2) the following entries replace those entries that have the same serial numbers:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6748	ex 0709 59 10	10	Fresh or chilled chanterelles for treatment other than simple repacking for retail sale ⁽¹⁾ ⁽²⁾	0 %	-	31.12.2025
0.2864	ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 10 ex 1513 29 30	20 20 20 20 20 20	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 19 10, — methyl esters of fatty acids of heading 2915 or 2916, — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, — stearic acid of subheading 3823 11 00, — goods of heading 3401, or — fatty acids with high purity of heading 2915 ⁽²⁾	0 %	-	31.12.2021
0.6789	ex 1512 19 10	10	Refined safflower oil (CAS RN 8001-23-8) for use in the manufacture of — conjugated linoleic acid of heading 3823 or — ethyl- or methyl esters of linoleic acid of heading 2916 ⁽²⁾	0 %	-	31.12.2022
0.5004	ex 2008 99 48	94	Mango puree: — not from concentrate, — of the genus <i>Mangifera</i> , — of a Brix value of 14 or more, but not more than 20, used in the manufacture of products of drink industry ⁽²⁾	6 %	-	31.12.2022
0.4709	ex 2008 99 49 ex 2008 99 99	30 40	Seedless boysenberry puree not containing added spirit, whether or not containing added sugar	0 %	-	31.12.2025
0.6723	ex 2008 99 91	20	Chinese water chestnuts (<i>Eleocharis dulcis</i> or <i>Eleocharis tuberosa</i>) peeled, washed, blanched, chilled and individually quick-frozen for use in the manufacture of products of food industry for treatment other than simple repacking ⁽¹⁾ ⁽²⁾	0 % ⁽³⁾	-	31.12.2025

0.4992	ex 2009 41 92 ex 2009 41 99	20 70	Pineapple juice: — not from concentrate, — of the genus <i>Ananas</i> , — of a Brix value of 11 or more but not more than 16, used in the manufacture of products of drink industry ⁽²⁾	8 %	-	31.12.2025
0.7393	ex 2712 90 99	10	Blend of 1-alkenes containing by weight 90 % or more 1-alkenes of a chain length of 24 carbon atoms or more but not more than 1 % 1-alkenes of a chain length of more than 70 carbon atoms	0 %	-	31.12.2022
0.6658	ex 2805 12 00	10	Calcium with a purity of 98 % or more by weight, in powder or wire form (CAS RN 7440-70-2)	0 %	-	31.12.2025
0.4979	2805 30 20 2805 30 30 2805 30 40		Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more	0 %	-	31.12.2025
0.6836	ex 2811 22 00	15	Amorphous silicon dioxide (CAS RN 60676-86-0) — in the form of powder — of a purity by weight of 99,0 % or more — with a median grain size of 0,7 µm or more, but not more than 2,1 µm — where 70 % of the particles have a diameter of not more than 3 µm	0 %	-	31.12.2022
0.5110	ex 2818 10 91	20	Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of: — 94 % or more, but less than 98,5 % of aluminium oxide, — 2 % (± 1,5 %) of magnesium oxide, — 1 % (± 0,6 %) of yttrium oxide, and — either 2 % (± 1,2 %) of lanthanum oxide, or — 2 % (± 1,2 %) of lanthanum oxide and neodymium oxide, with less than 50 % of the total weight having a particle size of more than 10 µm	0 %	-	31.12.2025
0.6837	ex 2818 30 00	20	Aluminium hydroxide (CAS RN 21645-51-2) — in the form of powder, — with a purity by weight of 99,5 % or more, — with a decomposition point of 263°C or more, — with a particle size of 4 µm (± 1 µm), — with a Total-Na ₂ O-content by weight of not more than 0,06 %	0 %	-	31.12.2025

0.7897	ex 2825 20 00	10	Lithium hydroxide monohydrate (CAS RN 1310-66-3)	2.6 %	-	31.12.2021
0.6819	ex 2825 50 00	30	Copper (II) oxide (CAS RN 1317-38-0), with a particle size of not more than 100 nm	0 %	-	31.12.2025
0.5055	ex 2826 19 90	10	Tungsten hexafluoride (CAS RN 7783-82-6) with a purity by weight of 99,9 % or more	0 %	-	31.12.2025
0.5090	ex 2833 29 80	30	Zirconium sulphate (CAS RN 14644-61-2)	0 %	-	31.12.2021
0.6632	ex 2840 20 90	10	Zinc borate (CAS RN 12767-90-7)	0 %	-	31.12.2025
0.7288	ex 2841 50 00	11	Potassium dichromate (CAS RN 7778-50-9) with a purity by weight of 99 % or more	2 %	-	31.12.2021
0.4222	ex 2841 90 85	10	Lithium cobalt(III) oxide (CAS RN 12190-79-3) with a cobalt content of at least 59 %	2.7 %	-	31.12.2021
0.3419	ex 2850 00 20	80	Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more	0 %	-	31.12.2024
0.6633	2903 39 21		Difluoromethane (CAS RN 75-10-5)	0 %	-	31.12.2025
0.2583	ex 2903 89 80	45	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 ^{6,9} .0 ^{2,13} .0 ^{5,10}] octadeca-7,15-diene (CAS RN 13560-89-9) with a purity by weight of 99 % or more	2 %	-	31.12.2021
0.6611	ex 2903 99 80	15	4-Bromo-2-chloro-1-fluorobenzene (CAS RN 60811-21-4)	0 %	-	31.12.2025
0.3409	ex 2904 20 00	10	Nitromethane (CAS RN 75-52-5)	0 %	-	31.12.2025
0.3391	ex 2904 20 00	20	Nitroethane (CAS RN 79-24-3)	0 %	-	31.12.2022
0.3408	ex 2904 20 00	30	1-Nitropropane (CAS RN 108-03-2)	0 %	-	31.12.2025
0.6612	ex 2904 99 00	25	Difluoromethanesulphonyl chloride (CAS RN 1512-30-7)	0 %	-	31.12.2025
0.6613	ex 2904 99 00	35	1-Fluoro-4-nitrobenzene (CAS RN 350-46-9)	0 %	-	31.12.2025
0.4934	ex 2905 39 95	10	Propane-1,3-diol (CAS RN 504-63-2)	0 %	-	31.12.2025
0.6757	ex 2906 29 00	40	2-Bromo-5-iodo-benzenemethanol (CAS RN 946525-30-0)	0 %	-	31.12.2022
0.6782	ex 2908 19 00	40	3,4,5-Trifluorophenol (CAS RN 99627-05-1)	0 %	-	31.12.2025
0.6915	ex 2908 19 00	50	4-Fluorophenol (CAS RN 371-41-5)	0 %	-	31.12.2025
0.6649	ex 2909 30 38	30	1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7)	0 %	-	31.12.2025

0.5117	ex 2909 30 90	30	3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)	0 %	-	31.12.2025
0.6614	ex 2909 30 90	40	1-Chloro-2,5-dimethoxybenzene (CAS RN 2100-42-7)	0 %	-	31.12.2025
0.6783	ex 2909 30 90	50	1-Ethoxy-2,3-difluorobenzene (CAS RN 121219-07-6)	0 %	-	31.12.2025
0.6784	ex 2909 30 90	60	1-Butoxy-2,3-difluorobenzene (CAS RN 136239-66-2)	0 %	-	31.12.2025
0.6927	ex 2909 49 80	10	1-Propoxypropan-2-ol (CAS RN 1569-01-3)	0 %	-	31.12.2021
0.6660	ex 2910 90 00	50	2,3-Epoxypropyl phenyl ether (CAS RN 122-60-1)	0 %	-	31.12.2025
0.5135	ex 2912 49 00	30	Salicylaldehyde (CAS RN 90-02-8)	0 %	-	31.12.2025
0.6678	ex 2912 49 00	40	3-Hydroxy-p-anisaldehyde (CAS RN 621-59-0)	0 %	-	31.12.2025
0.4933	ex 2914 29 00	30	(R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)	0 %	-	31.12.2025
0.4932	ex 2914 50 00	20	3'-Hydroxyacetophenone (CAS RN 121-71-1)	0 %	-	31.12.2025
0.6762	ex 2914 50 00	75	7-Hydroxy-3,4-dihydro-1(2H)-naphthalenone (CAS RN 22009-38-7)	0 %	-	31.12.2022
0.4948	ex 2914 79 00	60	4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)	0 %	-	31.12.2021
0.5119	ex 2915 39 00	60	Dodec-8-enyl acetate (CAS RN 28079-04-1)	0 %	-	31.12.2025
0.5121	ex 2915 39 00	65	Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)	0 %	-	31.12.2025
0.5120	ex 2915 39 00	70	Dodec-9-enyl acetate (CAS RN 16974-11-1)	0 %	-	31.12.2025
0.7541	ex 2915 90 30	10	Methyl laurate (CAS RN 111-82-0)	0 %	-	31.12.2025
0.4954	ex 2915 90 70	60	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)	0 %	-	31.12.2025
0.3466	ex 2916 13 00	30	Zinc monomethacrylate powder (CAS RN 63451-47-8) whether or not containing not more than 17 % by weight of manufacturing impurities	0 %	-	31.12.2025
0.4931	ex 2916 20 00	60	3-Cyclohexylpropionic acid (CAS RN 701-97-3)	0 %	-	31.12.2025
0.4930	ex 2916 39 90	30	2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)	0 %	-	31.12.2025
0.6794	ex 2916 39 90	41	4-Bromo-2,6-difluorobenzoyl chloride (CAS RN 497181-19-8)	0 %	-	31.12.2025
0.6661	ex 2916 39 90	53	5-Iodo-2-methylbenzoic acid (CAS RN 54811-38-0)	0 %	-	31.12.2025
0.4918	ex 2917 19 80	50	Tetradecanedioic acid (CAS RN 821-38-5)	0 %	-	31.12.2025
0.4945	ex 2917 39 95	20	Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)	0 %	-	31.12.2025

0.6796	ex 2917 39 95	25	Naphthalene-1,8-dicarboxylic anhydride (CAS RN 81-84-5)	0 %	-	31.12.2025
0.3640	ex 2917 39 95	30	Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)	0 %	-	31.12.2025
0.6800	ex 2917 39 95	35	1-Methyl-2-nitroterephthalate (CAS RN 35092-89-8)	0 %	-	31.12.2025
0.6814	ex 2918 99 90	13	3-Methoxy-2-methylbenzoyl chloride (CAS RN 24487-91-0)	0 %	-	31.12.2025
0.6901	ex 2918 99 90	18	Ethyl 2-hydroxy-2-(4-phenoxyphenyl)propanoate (CAS RN 132584-17-9)	0 %	-	31.12.2025
0.6747	ex 2918 99 90	85	Trinexapac-Ethyl (ISO) (CAS RN 95266-40-3) with a purity by weight of 96 % or more	0 %	-	31.12.2025
0.5038	ex 2920 29 00	20	Tris(methylphenyl)phosphite (CAS RN 25586-42-9)	0 %	-	31.12.2025
0.5045	ex 2920 29 00	40	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)	0 %	-	31.12.2025
0.7559	ex 2920 90 10	15	Ethyl methyl carbonate (CAS RN 623-53-0)	3.2 %	-	31.12.2021
0.6598	ex 2920 90 70	80	Bis(pinacolato)diboron (CAS RN 73183-34-3)	0 %	-	31.12.2025
0.4917	ex 2921 29 00	40	Decamethylenediamine (CAS RN 646-25-3)	0 %	-	31.12.2025
0.4862	ex 2921 30 99	30	1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)	0 %	-	31.12.2021
0.5124	ex 2921 43 00	60	3-Aminobenzotrifluoride (CAS RN 98-16-8)	0 %	-	31.12.2025
0.6825	ex 2921 49 00	60	2,6-Diisopropylaniline (CAS RN 24544-04-5)	0 %	-	31.12.2025
0.6947	ex 2922 19 00	35	2-[2-(Dimethylamino)ethoxy] ethanol (CAS RN 1704-62-7)	0 %	-	31.12.2025
0.6624	ex 2922 29 00	30	1,2-Bis(2-aminophenoxy)ethane (CAS RN 52411-34-4)	0 %	-	31.12.2025
0.6634	ex 2922 29 00	63	Aclonifen (ISO) (CAS RN 74070-46-5) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.4956	ex 2922 29 00	75	4-(2-Aminoethyl)phenol (CAS RN 51-67-2)	0 %	-	31.12.2025
0.4914	ex 2922 39 00	20	2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)	0 %	-	31.12.2025
0.6761	ex 2922 39 00	35	5-Chloro-2-(methylamino)benzophenone (CAS RN 1022-13-5)	0 %	-	31.12.2025
0.7853	ex 2922 49 85	13	Benzyl glycinate—4-methylbenzene-1-sulfonic acid (1/1) (CAS RN 1738-76-7) with a purity by weight of 93 % or more	0 %	-	31.12.2024
0.5037	ex 2922 49 85	17	Glycine (CAS RN 56-40-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8)	0 %	-	31.12.2025
0.6948	ex 2922 49 85	30	Aqueous solution containing 40 % by weight or more of sodium methylaminoacetate (CAS RN 4316-73-8)	0 %	-	31.12.2021

0.6650	ex 2922 49 85	65	Diethyl aminomalonate hydrochloride (CAS RN 13433-00-6)	0 %	-	31.12.2025
0.5063	ex 2923 90 00	75	Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — 35 % (\pm 0,5 %) by weight of tetraethylammonium hydroxide, — not more than 1 000 mg/kg of chloride, — not more than 2 mg/kg of iron, and — not more than 10 mg/kg of potassium	0 %	-	31.12.2025
0.3689	ex 2924 19 00	23	Acrylamide (CAS RN 79-06-1) with a purity by weight of 97 % or more	2 %	-	31.12.2021
0.5066	ex 2924 29 70	40	N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)	0 %	-	31.12.2025
0.5127	ex 2924 29 70	45	Propoxur (ISO) (CAS RN 114-26-1)	0 %	-	31.12.2025
0.5069	ex 2924 29 70	55	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 24304-50-5)	0 %	-	31.12.2025
0.6767	ex 2924 29 70	62	2-Chlorobenzamide (CAS RN 609-66-5)	0 %	-	31.12.2025
0.6766	ex 2924 29 70	64	N-(3',4'-dichloro-5-fluoro[1,1'-biphenyl]-2-yl)acetamide (CAS RN 877179-03-8)	0 %	-	31.12.2025
0.6934	ex 2926 90 70	17	Cypermethrin (ISO) with its stereoisomers (CAS RN 52315-07-8) with a purity by weight of 90 % or more	0 %	-	31.12.2025
0.6259	ex 2926 90 70	26	Cyfluthrin (ISO) (CAS RN 68359-37-5) with a purity by weight of 95,5 % or more for the use in the manufacture of biocidal products (?)	0 %	-	31.12.2024
0.6871	ex 2928 00 90	23	Metobromuron (ISO) (CAS RN 3060-89-7) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.4929	ex 2928 00 90	25	Acetaldehyde oxime (CAS RN 107-29-9) in an aqueous solution	0 %	-	31.12.2025
0.6635	ex 2928 00 90	50	Aqueous solution of 2,2'-(hydroxyimino) bisethanesulphonic acid disodium salt (CAS RN 133986-51-3) with a content by weight of more than 33,5 % but not more than 36,5 %	0 %	-	31.12.2025
0.5035	ex 2930 90 98	10	2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)	0 %	-	31.12.2022
0.6769	ex 2930 90 98	22	Tembotrione (ISO) (CAS RN 335104-84-2) with a purity by weight of 94,5 % or more	0 %	-	31.12.2025
0.6873	ex 2930 90 98	26	Folpet (ISO)(CAS RN 133-07-3) with a purity by weight of 97,5 % or more	0 %	-	31.12.2025

0.6617	ex 2930 90 98	53	Bis(4-chlorophenyl) sulphone (CAS RN 80-07-9)	0 %	-	31.12.2025
0.5114	ex 2930 90 98	55	Thiourea (CAS RN 62-56-6)	0 %	-	31.12.2025
0.6917	ex 2931 90 00	63	Chloroethenyldimethylsilane (CAS RN 1719-58-0)	0 %	-	31.12.2021
0.6946	ex 2931 90 00	65	Bis(4-tert-butylphenyl)iodonium hexafluorophosphate (CAS RN 61358-25-6)	0 %	-	31.12.2021
0.6620	ex 2932 20 90	65	Sodium 4-(methoxycarbonyl)-5-oxo-2,5-dihydrofuran-3-olate (CAS RN 1134960-41-0)	0 %	-	31.12.2025
0.7639	ex 2932 99 00	27	(2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4) with a purity by weight of 99 % or more	0 %	-	31.12.2023
0.4907	ex 2932 99 00	50	7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)	0 %	-	31.12.2021
0.6771	ex 2932 99 00	65	4,4-Dimethyl-3,5,8-trioxabicyclo[5,1,0]octane (CAS RN 57280-22-5)	0 %	-	31.12.2025
0.7811	ex 2933 19 90	33	Fipronil (ISO) (CAS RN 120068-37-3) with a purity by weight of 95 % or more for the use in the manufacture of veterinary medicine (?)	0 %	-	31.12.2024
0.6835	ex 2933 21 00	55	1-Aminohydantoin hydrochloride (CAS RN 2827-56-7)	0 %	-	31.12.2025
0.5115	ex 2933 21 00	80	5,5-Dimethylhydantoin (CAS RN 77-71-4)	0 %	-	31.12.2025
0.6812	ex 2933 39 99	14	N,4-Dimethyl-1-(phenylmethyl)- 3-piperidinamine hydrochloride (1:2) (CAS RN 1228879-37-5)	0 %	-	31.12.2022
0.4842	ex 2933 39 99	20	Copper pyrithione powder (CAS RN 14915-37-8)	0 %	-	31.12.2021
0.6813	ex 2933 39 99	26	2-[4-(Hydrazinylmethyl)phenyl]-pyridine dihydrochloride (CAS RN 1802485-62-6)	0 %	-	31.12.2022
0.5129	ex 2933 39 99	85	2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)	0 %	-	31.12.2025
0.6773	ex 2933 49 10	50	1-Cyclopropyl-6,7,8-trifluoro-1,4-dihydro-4-oxo-3-quinolinecarboxylic acid (CAS RN 94695-52-0)	0 %	-	31.12.2025
0.4927	ex 2933 49 90	30	Quinoline (CAS RN 91-22-5)	0 %	-	31.12.2025
0.6763	ex 2933 59 95	21	N-(2-oxo-1,2-dihydropyrimidin-4-yl)benzamide (CAS RN 26661-13-2)	0 %	-	31.12.2025
0.6677	ex 2933 59 95	47	6-Methyl-2-oxoperhydropyrimidin-4-ylurea (CAS RN 1129-42-6) with a purity of 94 % or more	0 %	-	31.12.2025

0.6774	ex 2933 69 80	13	Metribuzin (ISO) (CAS RN 21087-64-9) with a purity by weight of 93 % or more	0 %	-	31.12.2025
0.6621	ex 2933 69 80	15	2-Chloro-4,6-dimethoxy-1,3,5-triazine (CAS RN 3140-73-6)	0 %	-	31.12.2025
0.6951	ex 2933 69 80	17	Benzoguanamine (CAS RN 91-76-9)	0 %	-	31.12.2021
0.5131	ex 2933 69 80	55	Terbutryn (ISO) (CAS RN 886-50-0)	0 %	-	31.12.2025
0.4957	ex 2933 69 80	60	Cyanuric acid (CAS RN 108-80-5)	0 %	-	31.12.2025
0.4985	ex 2933 79 00	70	(S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2)	0 %	-	31.12.2025
0.6872	ex 2933 99 80	16	Pyridate (ISO)(CAS RN 55512-33-9) with a purity by weight of 90 % or more	0 %	-	31.12.2025
0.6829	ex 2933 99 80	21	1-(Bis(dimethylamino)methylene)-1H-[1,2,3]triazolo[4,5-b]pyridinium 3-oxide hexafluorophosphate(V) (CAS RN 148893-10-1)	0 %	-	31.12.2025
0.6599	ex 2933 99 80	54	3-(Salicyloylamino)-1,2,4-triazole (CAS RN 36411-52-6)	0 %	-	31.12.2025
0.6933	ex 2933 99 80	87	Carfentrazone-ethyl (ISOM) (CAS RN 128639-02-1) with a purity by weight of 90 % or more	0 %	-	31.12.2025
0.4955	ex 2934 20 80	60	Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)	0 %	-	31.12.2022
0.4910	ex 2934 20 80	70	N,N-Bis(1,3-benzothiazol-2-ylsulphonyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)	0 %	-	31.12.2025
0.4942	ex 2934 99 90	25	2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)	0 %	-	31.12.2025
0.6824	ex 2934 99 90	39	4-(Oxiran-2-ylmethoxy)-9H-carbazole (CAS RN 51997-51-4)	0 %	-	31.12.2025
0.6823	ex 2934 99 90	41	11-[4-(2-Chloro-ethyl)-1-piperazinyl]dibenzo(b,f)(1,4)thiazepine (CAS RN 352232-17-8)	0 %	-	31.12.2025
0.6893	ex 2934 99 90	44	Propiconazole (ISO) (CAS RN 60207-90-1) with a purity by weight of 92 % or more	0 %	-	31.12.2025
0.5133	ex 2934 99 90	86	Dithianon (ISO) (CAS RN 3347-22-6)	0 %	-	31.12.2025
0.5136	ex 2934 99 90	87	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)	0 %	-	31.12.2025
0.5036	ex 2935 90 90	42	Penoxsulam (ISO) (CAS RN 219714-96-2)	0 %	-	31.12.2025
0.6777	ex 2935 90 90	54	Propoxycarbazone-sodium (ISO) (CAS RN 181274-15-7) with a purity by weight of 95 % or more	0 %	-	31.12.2025

0.6802	ex 2935 90 90	56	N-(p-Toluenesulphonyl)-N'-(3-(p-toluenesulphonyloxy)phenyl)urea (CAS RN 232938-43-1)	0 %	-	31.12.2025
0.6903	ex 2935 90 90	57	N-{2-[(phenylcarbamoyl)amino]phenyl}benzenesulphonamide (CASRN 215917-77-4)	0 %	-	31.12.2025
0.6664	ex 2935 90 90	59	Flazasulfuron (ISO) (CAS RN 104040-78-0) with a purity of 94 % by weight or more	0 %	-	31.12.2025
0.4944	ex 2938 90 30	10	Ammonium glycyrrhizate (CAS RN 53956-04-0)	0 %	-	31.12.2025
0.6600	ex 3201 90 90 ex 3202 90 00	40 10	Reaction product of <i>Acacia mearnsii</i> extract, ammonium chloride and formaldehyde (CAS RN 85029-52-3)	0 %	-	31.12.2021
0.5091	ex 3204 11 00	20	Colourant C.I. Disperse Yellow 241 (CAS RN 83249-52-9) and preparations based thereon with a colourant C.I. Disperse Yellow 241 content of 97 % or more by weight	0 %	-	31.12.2021
0.5134	ex 3204 11 00	45	Preparation of dispersion dyes, containing: — C.I. Disperse Orange 61 (CAS RN 12270-45-0) or Disperse Orange 288 (CAS RN 96662-24-7), — C.I. Disperse Blue 291:1 (CAS RN 872142-01-3), — C.I. Disperse Violet 93:1 (CAS RN 122463-28-9), whether or not containing C.I. Disperse Red 54 (CAS RN 6657-37-0)	0 %	-	31.12.2025
0.6652	ex 3204 12 00	70	Colourant C.I. Acid blue 25 (CAS RN 6408-78-2) and preparations based thereon with a colourant C.I. Acid blue 25 content of 80 % or more by weight	0 %	-	31.12.2025
0.6603	ex 3204 17 00	33	Colourant C.I. Pigment Blue 15:1 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:1 content of 35 % or more by weight	0 %	-	31.12.2025
0.5100	ex 3204 19 00	73	Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight	0 %	-	31.12.2021
0.6726	ex 3208 90 19	55	Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic anhydride in an organic solvent	0 %	-	31.12.2021
0.5031	ex 3215 90 70	40	Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with: — wax — a vinyl-based polymer and — a colouring agent for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices (?)	0 %	-	31.12.2025

0.4863	ex 3402 11 90	10	Sodium lauroyl methyl isethionate	0 %	-	31.12.2021
0.6725	ex 3506 91 90	50	Preparation containing by weight: — 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers, and — 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers, dissolved in: — Methyl ethyl ketone (CAS RN 78-93-3), — Heptane (CAS RN 142-82-5), and — Toluene (CAS RN 108-88-3) or light aliphatic solvent naphtha (CAS RN 64742-89-8)	0 %	-	31.12.2021
0.6759	ex 3802 10 00	10	Mixture of activated carbon and polyethylene, in form of powder	0 %	-	31.12.2025
0.6874	ex 3808 92 30	10	Mancozeb (ISO) (CAS RN 8018-01-7) imported in immediate packings of a content of 500 kg or more ⁽¹⁾	0 %	-	31.12.2025
0.5048	ex 3808 93 90	20	Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight: — 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine of a kind used in plant growth regulators	0 %	-	31.12.2025
0.5030	ex 3808 93 90	30	Aqueous solution containing by weight: — 1,8 % of sodium para-nitrophenolate, — 1,2 % of sodium ortho-nitrophenolate, — 0,6 % of sodium 5-nitroguaiacolate, for use in the manufacture of a plant growth regulator ⁽²⁾	0 %	-	31.12.2022
0.5088	ex 3808 93 90	50	Preparation in the form of powder, containing by weight: — 55 % or more of Gibberellin A4, — 1 % or more but not more than 35 % of Gibberellin A7, — 90 % or more of Gibberellin A4 and Gibberellin A7 combined, — not more than 10 % of a combination of water and other naturally occurring Gibberellins, of a kind used in plant growth regulators	0 %	-	31.12.2021
0.6532	ex 3808 94 20	30	Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing: — 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5),	0 %	-	31.12.2024

			<ul style="list-style-type: none"> — 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5), — 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2), and/or — 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7) 			
0.6904	ex 3811 21 00	12	<p>Dispersing agent containing :</p> <ul style="list-style-type: none"> — esters of polyisobutenyl succinic acid and pentaerythritol (CAS RN 103650-95-9), — 35 % or more but not more than 55 % by weight of mineral oils, and — with a chlorine content of not more than 0,05 % by weight, <p>used in the manufacture of blends of additives for lubricating oils (?)</p>	0 %	-	31.12.2025
0.6906	ex 3811 21 00	14	<p>Dispersing agent :</p> <ul style="list-style-type: none"> — containing polyisobutene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 147880-09-9), — containing 35 % or more but not more than 55 % by weight of mineral oils, — with a chlorine content by weight of not more than 0,05 %, — having a total base number of less than 15, <p>used in the manufacture of blends of additives for lubricating oils (?)</p>	0 %	-	31.12.2025
0.6907	ex 3811 21 00	16	<p>Detergent containing :</p> <ul style="list-style-type: none"> — Calcium salt of beta-aminocarbonyl alkylphenol (reaction product Mannich base of alkylphenol) — 40 % or more but not more than 60 % by weight of mineral oils and — having a total base number more than 120 <p>used in the manufacture of blends of additives for lubricating oils (?)</p>	0 %	-	31.12.2025
0.6905	ex 3811 21 00	18	<p>Detergent containing :</p> <ul style="list-style-type: none"> — long chain alkyltoluene calcium sulphonates, — more than 30 % but not more than 50 % by weight of mineral oils, and — having a total base number of more than 310 but not more than 340, <p>used in the manufacture of blends of additives for lubricating oils (?)</p>	0 %	-	31.12.2025

0.6671	ex 3811 21 00	75	Additives containing: — Calcium (C10-C14) dialkylbenzenesulfonates, — more than 40 %, but not more than 60 % by weight of mineral oils, with a total base number of not more than 10, for use in the manufacture of blends of additives for lubricating oils (?)	0 %	-	31.12.2022
0.6669	ex 3811 21 00	77	Antifoam additives consisting of: — a copolymer of 2-ethylhexyl acrylate and ethyl acrylate, and — more than 50 % but not more than 80 % by weight of mineral oils, for use in the manufacture of additive blends for lubricating oils (?)	0 %	-	31.12.2022
0.6666	ex 3811 21 00	80	Additives containing : — polyisobutylene aromatic polyamine succinimide, — more than 40 % but not more than 60 % by weight of mineral oils, with a nitrogen content of more than 0,6 % but not more than 0,9 % by weight, for use in the manufacture of additive blends for lubricating oils (?)	0 %	-	31.12.2022
0.6668	ex 3811 29 00	65	Additives consisting of a sulphurised mixture of vegetable oil, long chain α -olefins and tall oil fatty acids, with a sulphur content of 8 % or more but not more than 12 % by weight, for use in the manufacture of blends of additives for lubricating oils (?)	0 %	-	31.12.2022
0.5062	ex 3815 90 90	30	Catalyst, consisting of a suspension in mineral oil of: — tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride, and — silicon dioxide, — containing 6,6 % (\pm 0,6 %) by weight of magnesium, and — containing 2,3 % (\pm 0,2 %) by weight of titanium	0 %	-	31.12.2025
0.2783	ex 3815 90 90	80	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	0 %	-	31.12.2025
0.6810	ex 3824 99 92	23	Butylphosphato complexes of titanium(IV) (CAS RN 109037-78-7), dissolved in ethanol and propan-2-ol	0 %	-	31.12.2025
0.4909	ex 3824 99 92	29	Preparation containing by weight: — 85 % or more but not more than 99 % of polyethylene glycol ether of butyl 2-cyano 3-(4-hydroxy-3-methoxyphenyl) acrylate, and — 1 % or more but not more than 15 % of polyoxyethylene (20) sorbitan trioleate	0 %	-	31.12.2025

0.6779	ex 3824 99 92	40	Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent	0 %	-	31.12.2025
0.7742	ex 3824 99 92	52	Electrolyte containing: — 5 % or more but not more than 20 % lithium hexafluorophosphate (CAS RN 21324-40-3) or lithium tetrafluoroborate (CAS RN 14283-07-9), — 60 % or more but not more than 90 % of a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and/or ethyl methyl carbonate (CAS RN 623-53-0), — 0,5 % or more but not more than 20 % 1,3,2-dioxathiolane 2,2-dioxide (CAS RN 1072-53-3), for use in the manufacture of motor vehicle batteries (?)	3.2 %	-	31.12.2021
0.5050	ex 3824 99 92	61	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine	0 %	-	31.12.2025
0.6720	ex 3824 99 92	68	Preparation containing by weight: — 20 % (± 1 %) ((3-(sec-butyl)-4-(decyloxy)phenyl)methanetriyl) Tribenzene (CAS RN 1404190-37-9) Dissolved in: — 10 % (± 5 %) 2-sec-Butylphenol (CAS RN 89-72-5) — 64 % (± 7 %) Solvent naphtha (petroleum), heavy aromatic (CAS RN 64742-94-5) and — 6 % ($\pm 1,0$ %) Naphthalene (CAS RN 91-20-3)	0 %	-	31.12.2025
0.6719	ex 3824 99 92	69	Preparation containing by weight: — 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) — 7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and — not more than 1 % triphenyl phosphate (CAS RN 115-86-6)	0 %	-	31.12.2021
0.3069	ex 3824 99 92	88	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated (CAS RN 9014-85-1)	0 %	-	31.12.2025
0.4719	ex 3824 99 93	35	Paraffin with a level of chlorination of 70 % or more (CAS RN 63449-39-8)	0 %	-	31.12.2024
0.7313	ex 3824 99 96	45	Lithium nickel cobalt aluminium oxide powder (CAS RN 177997-13-6) with: — a particle size of less than 10 μm , — a purity by weight of more than 98 %	3.2 %	-	31.12.2021

0.6628	ex 3824 99 96	46	Manganese zinc ferrite granulate, containing by weight: — 52 % or more but not more than 76 % of iron(III)oxide, — 13 % or more but not more than 42 % of manganese oxide, and — 2 % or more but not more than 22 % of zinc oxide	0 %	-	31.12.2025
0.6749	ex 3824 99 96	48	Zirconium oxide (ZrO ₂), calcium oxide stabilised (CAS RN 68937-53-1) with a zirconium oxide content by weight of 92 % or more but not more than 97 %	0 %	-	31.12.2025
0.6897	ex 3901 40 00	30	Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with: — more than 10 % but not more than 20 % by weight of copolymer, — a melt flow rate (MFR 190 °C/2,16 kg) of 0,7 g/10 min or more but not more than 0,9 g/10 min, and — a density (ASTM D4703) of 0,911 g/cm ³ or more, but not more than 0,913 g/cm ³ , for use in the co-extrusion processing of films for flexible food packaging (*)	0 %	m ³	31.12.2025
0.6920	ex 3901 90 80	53	Copolymer of ethylene and acrylic acid (CAS RN 9010-77-9) with: — an acrylic acid content of 18,5 % or more, but not more than 49,5 % by weight (ASTM D4094), and — a melt flow rate of 10g/10 min or more (125 °C/2,16 kg, ASTM D1238)	0 %	m ³	31.12.2025
0.6734	ex 3901 90 80	55	Zinc or sodium salt of an ethylene and acrylic acid copolymer, with: — an acrylic acid content of 6 % or more but not more than 50 % by weight, and — a melt flow rate of 1g/10 min or more at 190 °C/2,16 kg (measured using ASTM D1238)	0 %	-	31.12.2025
0.5049	ex 3901 90 80	67	Copolymer made exclusively from ethylene and methacrylic acid monomers in which the methacrylic acid content is 11 % by weight or more	0 %	-	31.12.2025
0.6736	ex 3903 90 90	65	Copolymer of styrene with 2, 5-furandione and (1-methylethyl)benzene in the form of flakes or powder (CAS RN 26762-29-8)	0 %	-	31.12.2025
0.6804	ex 3903 90 90	70	Copolymer in the form of granules containing by weight: — 75 % (± 7 %) styrene and — 25 % (± 7 %) methylmethacrylate	0 %	m ³	31.12.2025

0.4981	ex 3904 69 80	81	Poly(vinylidene fluoride) (CAS RN 24937-79-9)	0 %	-	31.12.2025
0.6672	ex 3906 90 90	33	Core shell copolymer of butyl acrylate and alkyl methacrylate, with a particle size of 5 µm or more but not more than 10 µm	0 %	-	31.12.2025
0.6663	ex 3906 90 90	37	Copolymer of trimethylolpropane trimethacrylate and methyl methacrylate (CAS RN 28931-67-1), in microsphere form with an average diameter of 3 µm	0 %	-	31.12.2025
0.6891	ex 3907 10 00	20	Polyoxymethylene with acetyl endcaps, containing polydimethylsiloxane and fibers of a copolymer of terephthalic acid and 1,4-phenyldiamine	0 %	-	31.12.2022
0.6839	ex 3907 30 00	15	Epoxide resin, halogen-free, — containing by weight more than 2 % phosphorous calculated on the solid content, chemically bound in the epoxide resin, — not containing any hydrolysable chloride or containing less than 300 ppm hydrolysable chloride, and — containing solvents, for use in the manufacture of prepreg sheets or rolls of a kind used for the production of printed circuits (?)	0 %	-	31.12.2025
0.6840	ex 3907 30 00	25	Epoxide resin — containing by weight 21 % or more of brome, — not containing any hydrolysable chloride or containing less than 500 ppm hydrolysable chloride, and — containing solvents	0 %	-	31.12.2025
0.4940	ex 3907 99 80 ex 3913 90 00	30 20	Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)	0 %	-	31.12.2025
0.5057	ex 3907 99 80	80	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles	0 %	-	31.12.2025
0.5032	ex 3909 40 00	20	Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices (?)	0 %	-	31.12.2025
0.6921	ex 3910 00 00	15	Dimethyl, methyl(propyl(polypropylene oxide)) siloxane (CAS RN 68957-00-6), trimethylsiloxy-terminated	0 %	-	31.12.2021
0.7217	ex 3910 00 00	45	Dimethyl siloxane, hydroxy-terminated polymer with a viscosity of 38-100 mPa·s (CAS RN 70131-67-8)	0 %	-	31.12.2021

0.5109	ex 3911 90 99	35	Alternated copolymer of ethylene and maleic anhydride (EMA)	0 %	-	31.12.2025
0.4953	ex 3912 11 00	40	Cellulose diacetate powder	0 %	-	31.12.2025
0.6718	ex 3912 39 85	50	Polyquaternium 10 (CAS RN 68610-92-4)	0 %	-	31.12.2025
0.4757	ex 3919 10 80	37	Polytetrafluoroethylene film: — with a thickness of 100 µm or more, — an elongation at break of not more than 100 %, — coated on one side with a pressure sensitive silicon adhesive	0 %	-	31.12.2025
0.4761	ex 3919 10 80 ex 3919 90 80	43 26	Ethylene vinyl acetate film: — of a thickness of 100 µm or more, — coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester or polypropylene liner	0 %	-	31.12.2022
0.6886	ex 3919 10 80	63	Reflecting film consisting of — a layer of an acrylic resin with imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, — a layer of an acrylic resin having embedded glass beads, — a layer of an acrylic resin hardened by a melamine cross-linking agent, — a metal layer, — an acrylic adhesive, and — a release film	0 %	-	31.12.2025
0.4947	ex 3919 90 80	65	Self-adhesive film with a thickness of 40 µm or more, but not more than 475 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner	0 %	-	31.12.2025
0.4925	ex 3919 90 80	70	Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad	0 %	-	31.12.2025
0.4964	ex 3919 90 80	82	Reflecting film consisting of: — a polyurethane layer, — a glass microspheres layer, — a metallised aluminium layer, and — an adhesive, covered on one or both sides with a release liner, — whether or not a poly(vinyl chloride) layer, — a layer whether or not incorporating security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use	0 %	-	31.12.2025

0.6640	ex 3920 10 40	40	Tubular layered film predominately of polyethylene: — consisting of a tri-layer barrier with a core layer of ethylene vinyl alcohol covered on either side with a layer of polyamide, covered on either side with at least one layer of polyethylene, — having a total thickness of 55 µm or more, — having a diameter of 500 mm or more but not more than 600 mm	0 %	-	31.12.2025
0.3357	ex 3920 62 19	48	Sheets or rolls of poly(ethylene terephthalate): — coated on both sides with a layer of epoxy acrylic resin, — of a total thickness of 37 µm (± 3 µm)	0 %	-	31.12.2025
0.2589	ex 3920 62 19	52	Film of polyethylene terephthalate, polyethylene naphthalate or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D257 method)	0 %	-	31.12.2023
0.6911	ex 3921 19 00	40	Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, with: — a width of 98 mm or more but not more than 170 mm, — a thickness of 15 µm or more but not more than 36 µm, of a kind used for the manufacture of alkaline battery separators	3.2 %	-	31.12.2021
0.7263	ex 3921 19 00	45	Microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with: — zero transversal production direction (TD) shrinkage, — a total thickness of 8 µm or more, but not more than 50 µm, — a width of 15 mm or more, but not more than 900 mm, — a length of more than 200 m, but not more than 8 000 m, — an average pore size between 0,02 µm and 0,1 µm, — laminated or not with a Polypropylene non-woven mat of 50 to 200 µm thickness, — coated or not with surfactant, — coated or not on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm, — coated or not on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm	3.2 %	-	31.12.2021

0.6742	ex 3921 90 55	40	Three layered fabric sheet, in rolls, — comprising a core layer of 100 % Nylon Taffeta or Nylon/Polyester blended Taffeta, — coated on both sides with polyamide, — of a total thickness not more than 135 µm, — of a total weight not more than 80 g/m ²	0 %	m ²	31.12.2025
0.7335	ex 3926 30 00 ex 3926 90 97	50 48	Coated interior or exterior decorative parts consisting of: — a copolymer of acrylonitrile-butadiene-styrene (ABS), whether or not mixed with polycarbonate, and — a PVC foil, — not containing layers of copper, nickel or chromium, for use in the manufacturing of parts for motor vehicles of heading 8701 to 8705 (?)	0 %	p/st	31.12.2022
0.6717	ex 3926 90 97	23	Plastic cover with clips for the exterior rear-view mirror of motor vehicles	0 %	p/st	31.12.2025
0.3850	ex 3926 90 97	43	Mixture of water and by weight 19 % or more but not more than 35 % of expanded hollow microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate or other methacrylate, of a diameter of 3 µm or more but not more than 4,95 µm	0 %	-	31.12.2023
0.6708	ex 4009 42 00	20	Rubber brake hose with: — textile strings, — a wall thickness of 3,2 mm, — a metal hollow terminal pressed on both ends, and — one or more mounting brackets, for use in the manufacture of goods of Chapter 87 (?)	0 %	-	31.12.2025
0.6844	ex 4016 93 00	30	Rectangular ethylene-propylene-diene rubber gasket, with: — a length of 72 mm or more but not more than 825 mm, — a width of 18 mm or more but not more than 155 mm, — a peak temperature of 150°C or more but not more than 240 °C, — a permissible material outflow at the place of the mold split of not more than 0,3 mm	0 %	-	31.12.2025
0.6884	ex 5403 39 00	10	Biodegradable (norm EN 14995) monofilament of not more than 33 dtex, containing at least 98 % by weight polylactide (PLA), for use in the manufacture of filtration fabrics for the food industry (?)	0 %	-	31.12.2022

0.5059	ex 5603 13 10	20	Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m ² but not more than 105 g/m ² and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)	0 %	m ²	31.12.2025
0.5987	ex 5603 14 90	60	Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — of weight of 160 g/m ² or more but not more than 300 g/m ² , — not laminated, — with filtration efficiency according to DIN 60335-2-69:2008 minimum Filter class M, — pleatable	0 %	m ²	31.12.2023
0.4978	ex 6909 19 00	20	Silicon nitride (Si ₃ N ₄) rollers or balls	0 %	-	31.12.2025
0.7619	ex 7006 00 90	40	Plates of sodalime or borosilicate glass of STN (Super Twisted Nematic) or TN (Twisted Nematic) quality having: — a length of 300 mm or more but not more than 1 500 mm, — a width of 300 mm or more but not more than 1 500 mm, — a thickness of 0,5 mm or more but not more than 1,1 mm, — an indium-tin-oxide coating with a resistance of 80 Ω or more, but not more than 160 Ω on one side, — with or without a passivation layer of silicon dioxide (SiO ₂) between indium-tin-oxide layer and glass surface, — with or without a multi layer anti-reflection-coating on the other side, and — machined (chamfered) edges	0 %	-	31.12.2023
0.6870	ex 7009 10 00	40	Electrochromic self-dimming inside rear-view mirror, consisting of: — a mirror support — a plastic casing and — an integrated circuit for use in the manufacture of motor vehicles of Chapter 87 (?)	0 %	-	31.12.2025
0.5021	ex 7019 19 10	20	Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 μm or more but not more than 5,83 μm predominate	0 %	-	31.12.2025
0.5020	ex 7019 19 10	25	Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 μm or more but not more than 5,83 μm predominate	0 %	-	31.12.2025

0.4853	ex 7202 99 80	10	Ferro-dysprosium, containing by weight: — 78 % or more of dysprosium, and — 18 % or more but not more than 22 % of iron	0 %	-	31.12.2025
0.7502	ex 7318 24 00	40	Tube or pipe restraint joint elements: — of stainless steel according to specification 17-4PH or of steel according to specification tool steel S7, — produced by metal injection moulding, — with a rockwell hardness of 38 HRC (± 1) or 53 HRC ($+ 2/- 1$), — measuring 7 mm x 4 mm x 5 mm or more, but not more than 40 mm x 20 mm x 10 mm	0 %	-	31.12.2023
0.6680	ex 7326 90 98	40	Iron and steel weights — whether or not with parts of other material — whether or not with parts of other metals — whether or not surface treated — whether or not printed of a kind used for the production of remote controls	0 %	-	31.12.2025
0.5029	ex 7604 29 10 ex 7606 12 99 ex 7606 12 99	10 21 25	Sheets and bars of aluminium-lithium alloys	0 %	-	31.12.2022
0.5487	ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 ex 7607 11 90	48 49 51 52 53 56	Aluminium foil in rolls: — having a purity of 99,99 % by weight, — of a thickness of 0,021 mm or more but not more than 0,2 mm, — with a width of 500 mm, — with a surface oxide layer by 3 to 4 nm thick, — and with a cubic texture of more than 95 %	0 %	-	31.12.2021
0.4050	ex 7607 11 90	60	Plain aluminium foil with the following parameters: — an aluminium content of 99,98 % or more, — a thickness of 0,070 mm or more but not more than 0,125 mm, — with a cubic texture, of a kind used for high voltage etching	3.7 %	-	31.12.2021
0.7698	ex 7607 20 90	10	Aluminium foil, in rolls: — coated on one side with polypropylene or polypropylene and acid-modified polypropylene and on the other with polyamide and polyethylene terephthalate, with adhesive layers between them,	3.7 %	-	31.12.2021

			<ul style="list-style-type: none"> — with a width of 200 mm or more, but not more than 400 mm, — with a thickness of 0,138 mm or more, but not more than 0,168 mm, for use in the manufacture of lithium-ion battery cell covers ⁽²⁾			
0.6730	ex 8101 96 00	10	Tungsten wire containing by weight 99 % or more of tungsten with: <ul style="list-style-type: none"> — a maximum cross-sectional dimension of not more than 50 µm — a resistance of 40 Ω or more but not more than 300 Ω at length of 1 metre 	0 %	-	31.12.2025
0.5097	ex 8104 30 00	35	Magnesium powder <ul style="list-style-type: none"> — of purity by weight of more than 99,5 % — with a particle size of 0,2 mm or more but not more than 0,8 mm 	0 %	-	31.12.2025
0.4904	ex 8108 90 30	45	Titanium-aluminium-vanadium alloy (TiAl6V4) wire, of a diameter less than 20 mm and complying with AMS standards 4928, 4965 or 4967	0 %	-	31.12.2025
0.6805	ex 8113 00 90	20	Cuboid spacer made of aluminium silicon carbide (AlSiC) composite used for packaging in IGBT-modules	0 %	-	31.12.2025
0.5024	ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8503 00 99 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97	30 40 30 50 43 40 55 70 55 22	Silicone or plastic keyboards, comprising: <ul style="list-style-type: none"> — parts of common metal, and — whether or not comprising parts of plastic, — epoxy resin reinforced with fiberglass or wood, — whether or not printed or surface-treated, — with or without electrical conductors, — with or without a membrane bonded to the keyboard, — with or without mono or multilayer protective film 	0 %	p/st	31.12.2025
0.4996	ex 8407 90 90	20	Compact Liquid Petroleum Gas (LPG) Engine System, with: <ul style="list-style-type: none"> — 6 cylinders, — an output of 75 kW or more, but not more than 80 kW, — inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427 ⁽²⁾	0 %	-	31.12.2025

0.6160	ex 8414 30 81 ex 8414 80 73	60 30	Hermetic rotary compressors for either hydrofluorocarbon (HFC) or hydrocarbon refrigerants: — driven by “on-off” single phase alternate current (AC) or “brushless direct current” (BLDC) variable speed motors, — with a nominal power rating of not more than 1,5 kW, — a rated voltage of 100 V or more but not more than 240 V, — with a height of not more than 300 mm, — an external diameter of not more than 150 mm, — with a unit weight of not more than 15 kg, for use in the manufacture of heat pumps for household appliances, including clothes dryers ^(?)	0 %	-	31.12.2023
0.7317	ex 8414 80 22	20	Air membrane compressor with: — a flow of 4,5 l/min or more, but not more than 7 l/min, — power input of not more than 8,1 W, and — a gauge pressure capacity not exceeding 400 hPa (0,4 bar), of a kind used in the production of motor vehicle seats	0 %	-	31.12.2022
0.6842	ex 8415 90 00	60	Flame-soldered aluminium block, for connecting tube with condenser in car air-conditioning systems, with: — extruded, bent connector lines of aluminium with an external diameter of 5 mm or more, but not more than 25 mm, — a weight of 0,02 kg or more but not more than 0,25 kg	0 %	p/st	31.12.2025
0.6860	ex 8415 90 00	65	Aluminium arc-welded removable receiver dryer, with polyamide and ceramic elements with: — a length of 143 mm or more but not more than 292 mm, — a diameter of 31 mm or more but not more than 99 mm, — with a weight of not less than 0,12 kg and not more than 0,9 kg, — a spangle length of not more than 0,2 mm and a thickness of not more than 0,06 mm, and — a solid particle diameter of not more than 0,06 mm, for use in the manufacture of car air-conditioning systems ^(?)	0 %	p/st	31.12.2022
0.6821	ex 8436 99 00	10	Part containing: — a single-phase AC motor, — an epicyclic gearing, — a cutter blade, and whether or not containing: — a capacitor, — a part fitted with a threaded bolt, for use in the manufacture of garden shredders ^(?)	0 %	p/st	31.12.2025

0.7380	ex 8481 80 59	30	Two-way flow control valve with housing, with: — at least 5, but not more than 16 outlet holes with at least 0,05 mm, but not more than 0,5 mm diameter, — at least 330 cm ³ /minute, but not more than 5 000 cm ³ /minute flow rate, — at least 19, but not more than 300 MPa operating pressure	0 %	-	31.12.2022
0.7518	ex 8481 90 00	40	Valve armature: — for the opening and closing of the flow of fuel, — consisting of a shaft and a blade, — with at least 3 but not more than 8 holes on the blade, — made of metal and/or metal alloy(s)	0 %	-	31.12.2023
0.4997	ex 8483 40 90	80	Transmission gearbox, with: — not more than 3 gears, — an automatic deceleration system, and — a power reversal system, for use in the manufacture of goods of heading 8427 (²)	0 %	p/st	31.12.2025
0.6854	ex 8501 10 10	20	Synchronous motor for a dishwasher with a water flow control mechanism with — a length without axle of 24 mm (\pm 0,3), — a diameter of 49,3 mm (\pm 0,3), — a rated voltage of 220 V AC or more but not more than 240 V AC, — a rated frequency of 50 Hz or more but not more than 60 Hz, — an input power of not more than 4 W, — a rotation speed of 4rpm or more but not more than 4,8rpm, — an output torque of not less than 10kgf/cm	0 %	-	31.12.2022
0.6858	ex 8501 10 99	64	DC motor to control angular position of the flap to adjust gas flow in the Air Throttle and EGR valve: — with Ingress Protection (IP) standard of IP69, — with a rotor speed of not more than 6 500 rpm when not loaded, — with a rated voltage of 12,0 V (\pm 0,1), — of a specified temperature range of - 40 °C or more, but not more than + 165 °C, — with or without a connecting pinion, — with or without an engine connector, — with or without a flange, — with a diameter of not more than 40 mm (not including the flange), — with an overall height of not more than 90 mm (from the base to the pinion)	0 %	-	30.06.2021

0.6880	ex 8501 10 99	65	Electric turbocharger actuator, with: <ul style="list-style-type: none"> — a DC motor, — an integrated gear mechanism, — a (pulling)force of 200 N or more at a minimum of 140 °C elevated ambient temperature, — a (pulling) force of 250 N or more in each position of its stroke, — an effective stroke of 15 mm or more but not more than 25 mm, — with or without an on-board diagnostics interface 	0 %	-	31.12.2025
0.6627	ex 8501 10 99	75	Permanently excited DC motor with <ul style="list-style-type: none"> — a multiple-phase winding, — an external diameter of 28 mm or more but not more than 35 mm, — a rated speed of not more than 12 000 rpm, — a power supply voltage of 8 V or more but not more than 27 V 	0 %	-	31.12.2025
0.4731	ex 8501 31 00	37	Permanently excited DC motor with <ul style="list-style-type: none"> — a multiple-phase winding, — an external diameter of 30 mm or more but not more than 90 mm, including mounting flange, — a rated speed of not more than 15 000 rpm, — an output of 45 W or more but not more than 400 W, and — a supply voltage of 9 V or more but not more than 50 V, — whether or not with a drive disc, — whether or not with a crankcase, — whether or not with a fan, — whether or not with a cap assembly, — whether or not with a sun gear, — whether or not with a speed and rotational direction encoder, — whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type, — whether or not with a mounting flange 	0 %	-	31.12.2024
0.5577	ex 8501 31 00	50	DC motors, brushless, with: <ul style="list-style-type: none"> — an external diameter of 80 mm or more, but not more than 200 mm, — a supply voltage of 9 V or more, but not more than 16 V, — an output at 20 °C of 300 W or more, but not more than 750 W, — a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm, 	0 %	-	31.12.2022

			<ul style="list-style-type: none"> — a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, — with or without a pulley, — with or without an electronic power steering sensor/controller 			
0.6809	ex 8501 31 00 ex 8501 32 00	53 45	Automotive-ready, brushless and permanently excited direct current motor with: <ul style="list-style-type: none"> — a specified speed of not more than 4 100 rpm, — a minimum output of 400 W, but not more than 1,3 kW (at 12 V), — a flange diameter of 85 mm or more, but not more than 200 mm, — a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, — a housing length of not more than 265 mm, measured from the flange to the outer ending, 	0 %	-	31.12.2025
			<ul style="list-style-type: none"> — a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), — a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and — surface magnets, — whether or not with electronic power steering controller 			
0.6161	ex 8503 00 99	55	Stator for brushless motor, with: <ul style="list-style-type: none"> — an internal diameter of 206,6 mm ($\pm 0,5$), — an external diameter of 265,0 mm ($\pm 0,2$), and — a width of 37,2 mm or more but not more than 47,8 mm, of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums	0 %	p/st	31.12.2025
0.7764	ex 8504 31 80	55	Electrical transformer with: <ul style="list-style-type: none"> — a capacity of 0,22 kVA or more, but not more than 0,24 kVA, — an operating temperature range of + 10°C or more, but not more than + 125° C, — four or five inductively coupled copper wire windings, — 11 or 12 connection pins at the bottom, and — dimensions of not more than 32 mm x 37,8 mm x 25,8 mm 	0 %	-	31.12.2024

0.7788	ex 8505 11 00	68	Blocks made of neodymium, iron and boron or an alloy of samarium and cobalt, whether or not covered with zinc, intended to become permanent magnets after magnetisation with: — a length of 13,8 mm or more but not more than 45,2 mm, — a width of 7,8 mm or more but not more than 25,2 mm, — a height of 1,3 mm or more but not more than 4,7 mm	0 %	-	31.12.2024
0.6857	ex 8505 11 00 ex 8505 19 90	73 35	Articles in shape of flat bars, arched bars or quarter sleeves, made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, whether or not overmolded with polymers, intended to become permanent magnets after magnetisation with: — a length of 5 mm or more, but not more than 60 mm, — a width of 5 mm or more, but not more than 40 mm, — a thickness of 3 mm or more, but not more than 15 mm	0 %	p/st	31.12.2022
0.7641	ex 8507 60 00	13	Prismatic lithium-ion electric accumulators with: — a width of 173,0 mm ($\pm 0,3$ mm), — a thickness of 45,0 mm ($\pm 0,3$ mm), — a height 125,0 mm ($\pm 0,3$ mm), — a nominal voltage of 3,67 V ($\pm 0,01$ V), and — a nominal capacity of 94 Ah and/or 120 Ah, for use in the manufacture of rechargeable electric vehicle batteries (?)	1.3 %	-	31.12.2021
0.6685	ex 8507 60 00	15	Cylindrical lithium-ion-accumulators or modules with: — a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, — a nominal voltage of 36 V or more, but not more than 48 V, — a power of 300 Wh or more, but not more than 648 Wh, for use in the manufacture of electric bicycles (?)	1.3 %	-	31.12.2021
0.6625	ex 8507 60 00	17	Lithium-ion starter accumulator, consisting of four rechargeable lithium-ion secondary cells, with: — a rated voltage of 12 V, — a length of 350 mm or more but not more than 355 mm, — a width of 170 mm or more but not more than 180 mm, — a height of 180 mm or more but not more than 195 mm, — weighing 10 kg or more but not more than 15 kg, — a nominal charge of 60 Ah or more, but not more than 80 Ah	1.3 %	-	31.12.2021
0.7663	ex 8507 60 00	18	Lithium-ion polymer accumulator equipped with a battery management system and can-bus interface with: — a length of not more than 1 600 mm, — a width of not more than 448 mm,	1.3 %	-	31.12.2021

			<ul style="list-style-type: none"> — a height of not more than 395 mm, — a nominal voltage of 280 V or more but not more than 400 V, — a nominal capacity of 9,7 Ah or more but not more than 10,35 Ah, — a charging voltage of 110 V or more but not more than 230 V, and — containing 6 modules with 90 cells or more but not more than 96 cells enclosed in a steel casing, <p>for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703 ⁽²⁾</p>			
0.7717	ex 8507 60 00	22	<p>Integrated battery system in a metal case with holders, consisting of:</p> <ul style="list-style-type: none"> — a lithium-ion battery with voltage of 48 V (\pm 5 V) and capacity of 0,44 kWh (\pm 0,05 kWh), — Battery Management System, — a relay, — a low voltage converter (DC/DC), — at least one connector, <p>for use in the manufacture of hybrid motor vehicles ⁽²⁾</p>	1.3 %	-	31.12.2021
0.2907	ex 8507 60 00	30	<p>Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries ⁽²⁾</p>	1.3 %	-	31.12.2021
0.6703	ex 8507 60 00	33	<p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> — a length of 150 mm or more, but not more than 1 000 mm, — a width of 100 mm or more, but not more than 1 000 mm, — a height of 200 mm or more, but not more than 1 500 mm, — a weight of 75 kg or more, but not more than 200 kg, — a nominal capacity not less than 150Ah and not more than 500 Ah, — a nominal output voltage of 230V AC (Line to neutral) or a nominal voltage of 64V (\pm10 %) 	1.3 %	-	31.12.2021
0.6702	ex 8507 60 00	37	<p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> — a length of 1 200 mm or more, but not more than 2 000 mm, — a width of 800 mm or more, but not more than 1 300 mm, — a height of 2 000 mm or more, but not more than 2 800 mm, — a weight of 1 800 kg or more, but not more than 3 000 kg, — a nominal capacity of 2 800 Ah or more but not more than 7 200 Ah 	1.3 %	-	31.12.2021

0.5548	ex 8507 60 00	50	Modules for the assembly of batteries of ion lithium electric accumulators with: — a length of 298 mm or more, but not more than 500 mm, — a width of 33,5 mm or more, but not more than 209 mm, — a height of 75 mm or more, but not more than 228 mm, — a weight of 3,6 kg or more, but not more than 17 kg, and — a nominal energy of 458 Wh or more, but not more than 2 158 Wh	1.3 %	-	31.12.2021
0.5342	ex 8507 60 00	65	Cylindrical lithium ion cell with — 3,5 VDC to 3,8 VDC, — 300 mAh to 900 mAh, and — a diameter of 10,0 mm to 14,5 mm	1.3 %	-	31.12.2021
0.7888	ex 8507 60 00	68	Lithium-ion accumulator in a metal housing, with — a length of 65 mm or more, but not more than 225 mm, — a width of 10 mm or more, but not more than 75 mm, — a height of 60 mm or more, but not more than 285 mm, — a nominal voltage of 2,1 V or more, but not more than 3,8 V, and — a nominal capacity of 2,5 Ah or more, but not more than 325 Ah	1.3 %	-	31.12.2021
0.5356	ex 8507 60 00	75	Rectangular lithium-ion-accumulator, with — a metal casing, — a length of 173 mm ($\pm 0,15$ mm), — a width of 21 mm ($\pm 0,1$ mm), — a height of 91 mm ($\pm 0,15$ mm), — a nominal voltage of 3,3 V, and — a nominal capacity of 21 Ah or more	1.3 %	-	31.12.2021
0.6753	ex 8507 60 00	77	Lithium-ion rechargeable batteries, with: — a length of 700 mm or more, but not more than 2 820 mm, — a width of 935 mm or more, but not more than 1 660 mm, — a height of 85 mm or more, but not more than 700 mm, — a weight of 250 kg or more, but not more than 700 kg, — a power of not more than 175 kWh, — a nominal voltage of 400 V	1.3 %	-	31.12.2021
0.5014	ex 8508 70 00 ex 8537 10 98	20 98	Electronic circuit cards that: — are connected by wire or radio frequency to each other and the motor controller card, and — regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program, — whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full)	0 %	p/st	31.12.2025

0.6856	ex 8512 20 00	30	Lighting module, containing at least: — two LEDs, — glass or plastic lenses, focusing/scattering the light emitted by the LEDs, — reflectors redirecting the light emitted by the LEDs, in an aluminium housing with a radiator, mounted at a bracket with an actuator	0 %	p/st	31.12.2025
0.6863	ex 8512 30 90	20	Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing: — a printed circuit board, — a connector, — whether or not a metal holder, for use in the manufacture of goods of Chapter 87 ^(?)	0 %	p/st	31.12.2022
0.6689	ex 8529 90 65	28	Electronic assembly comprising at least: — a printed circuit board with, — one or more FPGAs (Field Programmable Gate Array) and/or processors for multi-media applications and video signal processing, — flash memory, — operating memory, — with or without one or more USB, HDMI, VGA-, RJ-45 and/or other multi-media interfaces, — sockets and plugs for connecting a LCD-display, a LED lighting and a control panel	0 %	p/st	31.12.2025
0.4893	ex 8529 90 65 ex 8529 90 92	65 53	Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module	0 %	p/st	31.12.2025
0.4890	ex 8529 90 92	25	LCD modules, not combined with touch screen facilities, solely consisting of: — one or more TFT glass or plastic cells, — a die cast heat sink, — a backlight unit, — one printed circuit board with micro controller, and — LVDS (Low Voltage Differential Signalling) interface, for use in the manufacture of radios for motor vehicles ^(?)	0 %	p/st	31.12.2025
0.6654	ex 8529 90 92	37	Fastening and covering ledges of aluminium alloy containing: — silicon and magnesium, — with a length of 300 mm or more but not more than 2 200 mm, specifically shaped for use in the manufacture of TV sets ^(?)	0 %	-	31.12.2025

0.6629	ex 8529 90 92	63	<p>LCD module</p> <ul style="list-style-type: none"> — with a diagonal measurement of the screen of 14,5 cm or more but not more than 38,5 cm, — with or without a touch screen, — with an LED backlight, — with a printed circuit board with EEPROM, microcontroller, LVDS receiver and other active and passive components, — with a plug for power supply and CAN and LVDS interfaces, — with or without electronic components for dynamic adjustments of colour, — in a housing, with or without mechanical, touch-sensitive or contactless control functions and with or without active cooling system, <p>suitable for installation in motor vehicles of Chapter 87 ⁽²⁾</p>	0 %	p/st	31.12.2025
0.5018	ex 8529 90 92	67	<p>Colour LCD display panel for LCD monitors of heading 8528:</p> <ul style="list-style-type: none"> — with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm, — with or without a touch screen, — with backlight, micro-controller, — with a CAN (Controller area network)-controller with one or more LVDS (Low-voltage differential signalling) interfaces and one or more CAN/power supply sockets or with an APIX (Automotive Pixel Link) controller with APIX interface, — in a housing with or without a heat sink at the back of the housing, — without a signal-processing module, — whether or not with haptic and acoustical feedback, <p>for use in the manufacture of vehicles of Chapter 87 ⁽²⁾</p>	0 %	p/st	31.12.2025
0.6781	ex 8529 90 92	85	<p>Colour LCD module in a housing:</p> <ul style="list-style-type: none"> — with a diagonal screen measurement of 14,48 cm or more but not more than 26 cm, — without touch screen, — with a backlight and micro-controller, — with a CAN (Controller Area Network) controller, an LVDS (Low-Voltage Differential Signalling) interface and a CAN/power connector, — without a signal processing module, — with control electronics for pixel addressing only, — with a motorised mechanism for moving the display screen, <p>for permanent installation in vehicles of Chapter 87 ⁽²⁾</p>	0 %	p/st	31.12.2025

0.6849	ex 8536 69 90	60	Electrical sockets and plugs with a length of not more than 12,7 mm or a diameter of not more than 10,8 mm, for use in the production of hearing aids and speech processors ⁽²⁾	0 %	p/st	31.12.2022
0.5028	ex 8536 69 90	84	Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528 ⁽²⁾	0 %	p/st	31.12.2025
0.6864	ex 8537 10 91	50	Fuse control module in a plastic housing with mounting brackets comprising: — sockets with or without fuses, — connecting ports, — a printed circuit board with embedded microprocessor, micro switch and relay, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2025
0.6889	ex 8537 10 98	35	Electronic control unit without memory, for a voltage of 12 V, for information exchange systems in vehicles (for connection of audio, telephony, navigation, camera and wireless car service) containing: — 2 rotary knobs — 27 or more pushbuttons — LED lights — 2 integrated circuits for receiving and sending of control signals via the LIN-bus	0 %	p/st	31.12.2025
0.6866	ex 8538 90 91 ex 8538 90 99	20 50	Interior antenna for a car door locking system, comprising: — an antenna module in a plastic housing, — a connection cable with a plug, — at least two mounting brackets, whether or not PCB including integrated circuits, diodes and transistors, for use in the manufacture of goods of Chapter 87 ⁽²⁾	0 %	p/st	31.12.2025
0.6710	ex 8544 30 00 ex 8544 42 90	60 50	Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and audio systems to a USB connector, for use in the manufacture of goods of Chapter 87 ⁽²⁾	0 %	-	31.12.2025
0.6867	ex 8544 30 00	85	Extension two-core cable with two connectors, containing at least: — a rubber grommet, — a metal attachment bracket, of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87	0 %	p/st	31.12.2025

0.6853	ex 8544 42 90	70	Electric conductors: — of a voltage of not more than 80 V, — with a length of not more than 120 cm, — fitted with connectors, for use in the manufacture of hearing aids, accessory kits and speech processors (²)	0 %	p/st	31.12.2025
0.6861	ex 8544 49 93	30	Electric conductors: — of a voltage of not more than 80 V, — of a platinum-iridium-alloy, — coated with poly(tetrafluoroethylene), — without connectors, for use in the manufacture of hearing aids, implants and speech processors (²)	0 %	m	31.12.2025
0.5002	ex 8545 90 90	40	Corrosion resistant, layered technical fibre substrate of a gas diffuser layer with: — controlled fibre length, flex strength, porosity, thermal conductance, electrical resistance, — a thickness of less than 600 µm, — a weight of less than 500 g/m²	0 %	m²	31.12.2021
0.6707	ex 8708 30 10 ex 8708 30 91	70 40	Ductile cast iron brake caliper jaw, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2025
0.6869	ex 8708 40 20 ex 8708 40 50	20 10	Automatic hydrodynamic gearbox — with a hydraulic torque converter, — without transfer box and cardan shaft, — whether or not with front differential, for use in the manufacture of motor vehicles of Chapter 87 (²)	0 %	p/st	31.12.2025
0.6648	ex 8708 50 20 ex 8708 50 99	20 10	Transmission shaft in carbon fibre reinforced plastics consisting of a unique piece without any joint in the middle — of a length of 1 m or more but not more than 2 m, — of a weight of 6 kg or more but not more than 9 kg	0 %	p/st	31.12.2025
0.6711	ex 8708 80 20 ex 8708 80 35	10 10	Upper strut insulator containing: — a metal holder with three mounting screws, and — a rubber bump, for use in the manufacture of goods of Chapter 87 (²)	0 %	p/st	31.12.2025
0.6859	ex 8708 91 20 ex 8708 91 99	30 30	Aluminium alloy inlet or outlet air tank manufactured to standard EN AC 42100 with: — an insulating area flatness of not more than 0,1 mm, — a permissible particle quantity of 0,3 mg per tank, — a distance between pores of 2 mm or more,	0 %	p/st	31.12.2025

			<ul style="list-style-type: none"> — pore sizes of not more than 0,4 mm, and — not more than 3 pores larger than 0,2 mm, of a kind used in heat exchangers for car cooling systems			
0.7716	ex 8708 91 35	20	Turbocharger cooling duct containing: <ul style="list-style-type: none"> — an aluminium alloy duct with at least one metal holder and at least two mounting holes, — a rubber pipe with clips, — a stainless steel flange highly resistant to corrosion [SUS430JIL], for use in the manufacture of compression ignition engines of motor vehicles ⁽²⁾	0 %	-	31.12.2024
0.6687	ex 8708 95 10 ex 8708 95 99	10 20	Inflatable safety cushion of high strength polyamide fibre: <ul style="list-style-type: none"> — sewn, — folded into three-dimensional packing form, fixed by thermal forming, or flat (unfolded) safety cushion with or without thermal forming 	0 %	p/st	31.12.2025
0.6688	ex 8708 95 10 ex 8708 95 99	20 30	Inflatable safety cushion of high strength polyamide fibre: <ul style="list-style-type: none"> — sewn, — folded, — with three-dimensionally applied silicone bonding for air bag cavity forming and load-regulated air bag sealing, — suitable for cool inflator technology 	0 %	p/st	31.12.2025
0.7581	ex 8708 50 20 ex 8708 50 99	60 15	Car transfer case with single input, dual output, to distribute torque between front and rear axles in an aluminium housing, with dimension of not more than 565 × 570 × 510 mm, comprising: <ul style="list-style-type: none"> — at least an actuator, — whether or not an interior distribution by chain 	0 %	-	31.12.2024
0.6686	ex 8714 10 90	10	<ul style="list-style-type: none"> — Motorcycle fork rod inner tubes: — of SAE1541 carbon steel, — with a hard chromium layer of 20 µm (+ 15 µm/ - 5 µm), — having a wall thickness of 1,3 mm or more, but not more than 1,6 mm, — having an elongation at break of 15 %, — perforated 	0 %	p/st	31.12.2025
0.6848	ex 8714 10 90	70	Motor bikes radiators in consignment of 100 pieces or more	0 %	p/st	31.12.2022
0.6879	ex 8714 96 10	10	Pedals, for use in the manufacture of bicycles (including electric bicycles) ⁽²⁾	0 %	-	31.12.2025

0.6878	ex 8714 99 90	30	Seat posts, for use in the manufacture of bicycles (including electric bicycles) ⁽²⁾	0 %	p/st	31.12.2025
0.4883	ex 9001 90 00	85	Light guide panel made of poly(methyl methacrylate): — whether or not cut, — whether or not printed, for use in the manufacture of backlight units for flat screen TVs ⁽²⁾	0 %	-	31.12.2025
0.7590	ex 9002 11 00	18	Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with: — a horizontal field of view range to a maximum of 120 deg, — a diagonal field of view range to a maximum of 92 deg, — a focal length to a maximum of 7,50 mm, — a relative aperture of a maximum of F/2,90, — a maximum diameter of 22 mm	0 %	-	31.12.2023
0.5692	ex 9002 11 00	20	Lenses: — measuring not more than 95 mm × 55 mm × 50 mm, — with a resolution of 160 lines/mm or better, and — with a zoom ratio of 3 or more times	0 %	-	31.12.2022
0.5025	ex 9401 90 80	10	Ratchet disk for use in the manufacture of reclining car seats ⁽²⁾	0 %	p/st	31.12.2025
0.4846	ex 9503 00 75 ex 9503 00 95	10 10	Plastic cable car scale models, whether or not with a motor, for printing ⁽²⁾	0 %	p/st	31.12.2025
0.6950	ex 9607 20 10	10	Sliders, narrow tape with mounted zipper teeth, pin/boxes and other parts of slide fasteners, of base metal for use in the manufacture of zippers ⁽²⁾	0 %	-	31.12.2022
0.6949	ex 9607 20 90	10	Narrow strips mounted with plastic chain scoops for use in the manufacture of zippers ⁽²⁾	0 %	-	31.12.2025

⁽¹⁾ However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.

⁽²⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).

⁽³⁾ Only the *ad valorem* duty is suspended. The specific duty shall continue to apply.;

(3) the following entries are added or inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8021	2804 70 10		Red phosphorus	0 %	-	31.12.2022
0.8022	2804 70 90		Phosphorus, other than red phosphorus	0 %	-	31.12.2023
0.7974	ex 2903 39 19	40	3-(Bromomethyl)pentane (CAS RN 3814-34-4) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8017	ex 2903 99 80	25	2,2'-Dibromobiphenyl (CAS RN 13029-09-9) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8018	ex 2903 99 80	35	2-Bromo-9,9'-spirobi[9H-fluoren] (CAS RN 171408-76-7) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7957	ex 2904 99 00	55	2,4-dichloro-1,3-dinitro-5-(trifluoromethyl)benzene (CAS RN 29091-09-6) with a purity by weight of 96 % or more	0 %	-	31.12.2025
0.7963	ex 2906 29 00	70	1,2,3,4-Tetrahydro-1-naphthol (CAS RN 529-33-9) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8015	ex 2914 29 00	35	4-(trans-4-Propylcyclohexyl)cyclohexanone (CAS RN 82832-73-3) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7955	ex 2915 24 00	10	Acetic anhydride (CAS RN 108-24-7) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7980	ex 2916 19 95	60	Methyl 2-fluoroprop-2-enoate (CAS RN 2343-89-7) with a purity by weight of 93 % or more, whether or not with not more than 7 % of the stabiliser 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0) and Tetrabutylammonium nitrite (CAS RN 26501-54-2)	0 %	-	31.12.2025
0.7940	ex 2916 19 95	70	Methyl 3-methyl-2-butenolate (CAS RN 924-50-5) with a purity by weight of 99,0 % or more	0 %	-	31.12.2025
0.7931	ex 2916 20 00	25	Cyclohexanecarbonyl chloride (CAS RN 2719-27-9) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.7933	ex 2916 20 00	35	2-Cyclopropylacetic acid (CAS RN 5239-82-7) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7929	ex 2916 39 90	16	3-Fluoro-5-iodo-4-methylbenzoic acid (CAS RN 861905-94-4) with a purity by weight of 97 % or more	0 %	-	31.12.2025

0.8008	ex 2918 29 00	40	3-Hydroxy-4-nitrobenzoic acid (CAS RN 619-14-7) with a purity by weight of more than 96,5 %	0 %	-	31.12.2025
0.7934	ex 2918 99 90	43	Vanillic acid (CAS RN 121-34-6) with a purity by weight of 98,5 % or more	0 %	-	31.12.2025
0.7947	ex 2921 29 00	70	N,N,N',N'-tetramethylethylenediamine (CAS RN 110-18-9) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8019	ex 2921 49 00	45	2-(4-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 897671-69-1) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8020	ex 2921 49 00	55	2-(2-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 1198395-24-2) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7946	ex 2922 19 00	29	N-Methyl-N-(2-hydroxyethyl)-p-toluidine (CAS RN 2842-44-6) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.7935	ex 2922 19 00	70	2-Benzylaminoethanol (CAS 104-63-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8000	ex 2924 19 00	18	2-(((Butylamino)carbonyl)oxy)ethyl acrylate (CAS RN 63225-53-6) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.8013	ex 2925 19 95	40	N-Iodosuccinimide (CAS RN 516-12-1) with a purity by weight of 98,5 % or more	0 %	-	31.12.2025
0.7985	ex 2930 90 98	88	1-{4-[(4-Benzoylphenyl)sulphonyl]phenyl}-2-methyl-2-[(4-methylphenyl)sulphonyl]propan-1-one (CAS RN 272460-97-6) with a purity by weight of 94 % or more	0 %	-	31.12.2025
0.7951	ex 2931 90 00	25	N-(3-(dimethoxymethylsilyl)propyl)ethylenediamine (CAS RN 3069-29-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7958	ex 2932 20 90	18	4-Hydroxycoumarin (CAS-RN 1076-38-6) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7984	ex 2932 20 90	23	1,4-Dioxane-2,5-dione (CAS RN 502-97-6) with a purity by weight of 99,5 % or more	0 %	-	31.12.2025
0.7978	ex 2932 99 00	68	3,9-Diethylidene-2,4,8,10-tetraoxaspiro[5.5]undecane (CAS RN 65967-52-4) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7930	ex 2932 99 00	73	5-Fluoro-3-methylbenzofuran-2-carboxylic acid (CAS RN 81718-76-5) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7936	ex 2932 99 00	78	Methyl 2,2-difluoro-1,3-benzodioxole-5-carboxylate (CAS RN 773873-95-3) with a purity by weight of 98 % or more	0 %	-	31.12.2025

0.7954	ex 2932 99 00	83	6,11-Dihydrodibenz[b,e]oxepin-11-one (CAS RN 4504-87-4) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7938	ex 2933 19 90	43	tert-Butyl 2-(3,5-dimethyl-1H-pyrazol-4-yl)acetate (CAS RN 1082827-81-3) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7937	ex 2933 29 90	23	1,1'-Thiocarbonylbis(imidazole) (CAS RN 6160-65-2) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7976	ex 2933 39 99	83	2-Hydroxy-4-azoniaspiro[3,5]nonane chloride (CAS RN 15285-58-2) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7925	ex 2933 39 99	84	Diethyl(3-pyridyl)borane (CAS RN 89878-14-8) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7981	ex 2933 39 99	86	3-(N-hydroxycarbamimidoyl)pyridine 1-oxide (CAS RN 92757-16-9) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7939	ex 2933 39 99	87	6-Chloro-N-(2,2-dimethylpropyl)pyridine-3-carboxamide (CAS RN 585544-20-3) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7986	ex 2933 39 99	88	Benzyl 4-amino-3-chloro-6-(4-chloro-2-fluoro-3-methoxyphenyl)-5-fluoropyridine-2-carboxylate (CAS RN 1390661-72-9) with a purity by weight of 92 % or more	0 %	-	31.12.2025
0.7952	ex 2933 69 80	33	2,4,6-Trichloro-1,3,5-triazine (CAS RN 108-77-0) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.7927	ex 2933 99 80	60	2-[(6,11-Dihydro-5H-dibenz[b,e]azepin-6-yl)-methyl]-1H-isoindole-1,3(2H)-dione (CAS RN 143878-20-0) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.7971	ex 2933 99 80	70	5-(Bis-(2-hydroxyethyl)-amino)-1-methyl-1H-benzimidazole-2-butanoic acid ethyl ester (CAS RN 3543-74-6) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8014	ex 2933 99 80	80	Pyrrole-2-carboxaldehyde (CAS RN 1003-29-8) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.7926	ex 2934 99 90	65	Benzo[b]thiophen-10-methoxycycloheptanone (CAS RN 59743-84-9) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.7944	ex 2934 99 90	70	1,3,4-thiadiazolidine-2,5-dithione (CAS RN 1072-71-5) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.7928	ex 2935 90 90	44	4-[2-(7-Methoxy-4,4-dimethyl-1,3-dioxo-3,4-dihydroisoquinolin-2(1H)-yl)ethyl]bezenesulphonamide (CAS RN 33456-68-7) with a purity by weight of 99,5 % or more	0 %	-	31.12.2025

0.7943	ex 3201 90 20	10	<i>Rhus chinensis</i> gall (<i>Galla chinensis</i>) water-based extract, with a tannin content by weight of 85 % or less	0 %	-	31.12.2025
0.7975	ex 3801 10 00	10	Artificial graphite in powder form, (CAS RN 7782-42-5) with: — a secondary particle structure which is aggregated from smaller primary particles, — without coating on the surface, — particle size represented by d50 value of 13,5 µm (± 0,5), — specific surface area (measured by BET) less than 2,0 m ² /g, — tap density: 1,10 ~ 1,70 g/cm ³ , — specific Discharge Capacity of 351,0 mAh/g (± 3,0), — initial efficiency of 94,0 % (± 1,0)	1.8 %	-	31.12.2021
0.7994	ex 3801 10 00	20	Artificial graphite (CAS RN 7782-42-5) powder form, with: — specific surface area (measured by BET) of 0,8 m ² /g (± 0,25), — tap density: 0,85 g/cm ³ (± 0,10), — particle size represented by d50 value of 21,0 µm (± 2,0), — specific discharge capacity of 351,0 mAh/g (± 3,0), — initial efficiency of 94,0 % (± 2,0)	1.8 %	-	31.12.2021
0.7998	ex 3815 90 90	38	Photoinitiator, containing by weight: — 80 % or more of polyethylene glycol di[β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate (CAS RN 886463-10-1), — not more than 17 % of polyethylene glycol [β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate	0 %	-	31.12.2025
0.7999	ex 3815 90 90	48	Photoinitiator containing by weight: — 88 % or more of α-(2-benzoylbenzoyl)-ω-[(2-benzoylbenzoyl)oxy]-poly(oxy-1,2-ethanediyl) (CAS RN 1246194-73-9), — not more than 12 % of α-(2-benzoylbenzoyl)-ω-hydroxy-poly(oxy-1,2-ethanediyl) (CAS RN 1648797-60-7)	0 %	-	31.12.2025
0.7950	ex 3902 90 90	65	Brominated butadiene-styrene copolymer (CAS RN 1195978-93-8) with a bromine content of 60 % by weight or more but not more than 68 %, in forms as defined in Note 6 (b) to Chapter 39	0 %	-	31.12.2025
0.7953	ex 3910 00 00	65	Liquid copolymer based on polydimethylsiloxane with terminal epoxide groups (CAS RN 2102536-93-4)	0 %	-	31.12.2025
0.8009	ex 3911 90 99	38	Mixture containing by weight: — 90 % (± 1 %) of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-,polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and	0 %	-	31.12.2025

			— 10 % (± 1 %) of a hydrogenated styrene butadiene copolymer (CAS RN 66070-58-4)			
0.8010	ex 3911 90 99	48	Mixture containing by weight: — 90 % (± 1 %) of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 10 % (± 1 %) of an ethylene-propylene copolymer (CAS RN 9010-79-1)	0 %	-	31.12.2025
0.7949	ex 3920 61 00	40	Extruded thermoplastic foils or films of polycarbonate with: — matt surface texture on both sides, — a thickness of more than 50 μm but not more than 200 μm , — a width of 800 mm or more, but not more than 1 500 mm, and — a length of 915 m or more, but not more 2 500 m, for use in the production of retroreflective products (!)	0 %	-	31.12.2025
0.8011	ex 3920 62 19 ex 3920 62 90	68 20	Poly(ethylene terephthalate) film in rolls: — with a thickness of 50 μm or more but not more than 350 μm , and — covered with a layer of sputtered precious metal such as gold or palladium with a thickness of 0,02 μm or more but not more than 0,06 μm	0 %	-	31.12.2025
0.8005	ex 3920 99 28	48	Thermoplastic polyurethane foil in rolls, with: — a width of 900 mm or more but not more than 1 016 mm, — a matt finish, — a thickness of 0,4 mm (± 8 %), — an elongation at break of 480 % or more (ASTM D412 (Die C)), — a tensile strength in machine direction of 470 (± 10) kg/cm^2 (ASTM D412 (Die C)), — a Shore A hardness of 90 (± 3) (ASTM D2240), — a tear strength of 100 (± 10) kg/cm^2 (ASTM D624 (Die C)), — a melting point of 165°C (± 10 °C)	0 %	-	31.12.2025
0.8024	ex 5603 14 10	20	Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — of weight of 160 g/m^2 or more but not more than 300 g/m^2 — laminated on one side with a membrane or a membrane and aluminium — with filtration efficiency according to DIN 60335-2-69:2008 minimum Filter class M — pleatable	0 %	m^2	31.12.2023

0.8028	ex 6909 19 00	40	Ceramic-carbon absorption cartridges with the following characteristics: — extruded fired ceramic bound multicellular cylindrical structure, — 10 % or more by weight but not more than 35 % by weight of activated carbon, — 65 % or more by weight but not more than 90 % by weight of ceramic binder, — with a diameter of 29 mm or more but not more than 41 mm, — a length of not more than 150 mm, — fired at temperature of 800 °C or more, and — for vapours adsorption, of a kind used for assembly in fuel vapours absorbers in fuel systems of motor vehicles	0 %	p/st	31.12.2025
0.7913	ex 7506 20 00	20	Sheets and strips in coils of nickel alloy to standard ASME SB-582/UNS N06030 with: — a thickness of 0,5 mm or more but not more than 3 mm, — a width of 250 mm or more but not more than 1 219 mm	0 %	-	31.12.2025
0.7997	ex 7616 99 90	35	Aluminium plate with: — a length of 36 mm or more but not more than 49 mm, — a width of 29,8 mm or more but not more than 45,2 mm, — a thickness of 0,18 mm or more but not more than 0,66 mm, equipped with a polypropylene tape with: — a length of 6,5 mm or more but not more than 16,5 mm, — a width of 39 mm or more but not more than 56 mm, — characteristic allowing to create solid joint with Pouch external layer by melting process assuring leak and pressure proof sealing of Cell, — resistance to influence of electrolyte, for use in the manufacture of lithium-ion battery cells for motor vehicle batteries ⁽¹⁾	3 %	-	31.12.2021
0.7966	ex 8104 19 00	10	Unwrought magnesium containing 93 % or more but not more than 99,7 % by weight of magnesium	0 %	-	31.12.2025
0.7942	ex 8108 90 30	35	Bars and wires of titanium with a titanium content of 98,8 % or more but not more than 99,9 % of a diameter less than 20 mm	0 %	-	31.12.2025
0.8012	ex 8406 82 00	10	Industrial steam turbine with: — an output of 5 MW or more but not more than 40 MW, — designed for a pressure of not more than 140 bar and a temperature of not more than 540 °C, — equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 12 bar	0 %	-	31.12.2025

0.7961	ex 8409 91 00 ex 8481 90 00	55 60	Nozzle body for the regulation of angle and distribution of fuel injection: — of a cylindrical shape, — made of stainless steel, — with 4 or more, but not more than 16 holes, — with a flow rate of 100 cm ³ /minute or more, but not more than 500 cm ³ /minute	0 %	-	31.12.2025
0.7965	ex 8409 91 00	75	Housing of fuel injection valve for generating an electromagnetic field to actuate the injection valve with: — an inlet diameter of 2 mm or more, but not more than 10 mm, — an outlet diameter of 2 mm or more, but not more than 10 mm, — an electric coil with a resistance of 10 Ω or more, but not more than 15 Ω, which ends in an electrical connection, — a plastic covering moulded around a stainless steel tube	0 %	-	31.12.2025
0.7967	ex 8409 91 00 ex 8481 90 00	80 70	Nozzle needle for opening and closing the flow of fuel in the engine, with: — 2 holes, — 4 grooves, — a diameter of 3 mm or more, but not more than 6 mm, — a length of 25 mm or more, but not more than 35 mm, — made of stainless steel with hard-chrome plating	0 %	-	31.12.2025
0.7969	ex 8413 30 20	40	High-pressure plunger pump for direct diesel injection, with: — an operating pressure of not more than 275 MPa, — a camshaft, — a fluid discharging of 15 cm ³ per minute or more, but not more than 1 800 cm ³ per minute, — an electric pressure regulating valve	0 %	-	31.12.2025
0.7970	ex 8413 30 20	50	High-pressure plunger pump for direct diesel injection: — with an operating pressure of not more than 275 MPa, — designed to contact the crankshaft, — with an electromagnetic valve	0 %	-	31.12.2025
0.7996	ex 8418 99 90	20	Aluminium connecting block for connecting to a condenser manifold in welding process: — hardened to T6 or T5 temper, — with a weight of not more than 150 g, — with a length of 20 mm or more but not more than 150 mm, — with a fixing rail in one piece	0 %	-	31.12.2025

0.8004	ex 8418 99 90	30	Receiver dryer profile for connecting to a condenser manifold in welding process with: — a braze flatness of not more than 0,2 mm, — a weight of 100 g or more but not more than 600 g, — a fixing rail in one piece	0 %	-	31.12.2025
0.7979	ex 8479 89 97	55	Integrated automated turnkey machinery line for manufacturing jelly rolls of cylindrical lithium ion battery cells by winding, tab assembly and cutting of cathode, separator and anode	0.8 %	-	31.12.2021
0.7982	ex 8479 89 97	65	Integrated automated turnkey machinery line for the assembly of battery cells to cylindrical lithium ion batteries with a speed of 300 parts per minute and production line	0.8 %	-	31.12.2021
0.7964	ex 8479 90 70	40	Housing of the rotor part of the mechanical unit ensuring the adjustment of movement of the camshaft compared to the crankshaft: — of a circular shape, — made of steel alloy with sintering process, — with not more than 8 oil chambers, — with a Rockwell hardness of 55 or more, — with a density of 6,5 g/cm ³ , or more, but not more than 6,7 g/cm ³	0 %	-	31.12.2025
0.7968	ex 8481 30 91 ex 8481 30 99	30 50	Mechanical check (non-return) valve for opening and closing of the flow of fuel: — with an operating pressure of not more than 250 MPa, — with a flow rate of 45 cm ³ /minute or more, but not more than 55 cm ³ /minute, — with 4 input holes, each of them with a diameter of 1,2 mm or more, but not more than 1,6 mm, — made of steel	0 %	-	31.12.2025
0.7960	ex 8481 80 59 ex 8481 90 00	70 80	Flow-control valve — made of steel, — with an outlet hole with a diameter of at least 0,05 mm, but not more than 0,5 mm, — with an inlet hole with a diameter of at least 0,1 mm, but not more than 1,3 mm	0 %	-	31.12.2025
0.7972	ex 8527 29 00 ex 8529 90 65	10 38	Satellite radio receiver module: — with a rectangular shape of dimensions 70,5 x 44,9 x 10,5 mm,	0 %	-	31.12.2025

			<ul style="list-style-type: none"> — comprising of heat sink and a printed circuit board with resistors, capacitors, transistors, coils, diodes and IC, — being able to process radio frequency signals, — with a medium frequency unit, for use in the manufacture of products falling under heading 8527 ⁽¹⁾			
0.7987	ex 8708 50 20 ex 8708 50 55	15 50	Spherical outboard constant velocity joint ball bearing cage, part of the vehicle's drive system, made of material suitable to be carburized with a carbon content of 0,14 % or more but not more than 0,57 %, forged, turned, punched, milled and hardened	0 %	-	31.12.2025
0.7988	ex 8708 50 20 ex 8708 50 99	25 45	Ball-type outboard constant velocity joint housing for transmitting a torque from the engine and transmission to the wheels of motor vehicles, in a form of an outer race, with: <ul style="list-style-type: none"> — 6 ball tracks or more but not more than 8, with — a thread, — an external involute spline with 21 or more but not more than 38 teeth, — for running with bearing balls made of steel with a carbon content of 0,48 % or more but not more than 0,57 %, — forged, turned, milled and hardened 	0 %	-	31.12.2025
0.7989	ex 8708 50 20 ex 8708 50 99	35 50	Inboard constant velocity joint tripod housing, with: <ul style="list-style-type: none"> — an outer diameter of 67,0 mm or more but not more than 99,0 mm, — 3 cold calibrated roller tracks with a diameter of 29,95 mm or more but not more than 49,2 mm, — an external spline with 21 teeth or more but not more than 41, — forged, turned, rolled and hardened 	0 %	-	31.12.2025
0.7990	ex 8708 50 20 ex 8708 50 99	45 55	Outboard constant velocity joint inner race, part of the vehicle's drive system, with: <ul style="list-style-type: none"> — 6 or more but not more than 8 ball tracks, suitable for bearing balls with a diameter of 12,0 mm or more but not more than 24,0 mm, — forged, turned, milled, broached and hardened 	0 %	-	31.12.2025
0.7991	ex 8708 50 20 ex 8708 50 99	55 60	Inboard constant velocity joint tripod spider, part of the vehicle's drive system, with: <ul style="list-style-type: none"> — 3 trunnions with a diameter of 17,128 mm or more but not more than 25,468 mm, — forged, turned, broached and hardened 	0 %	-	31.12.2025

0.7973	ex 9002 11 00	23	Lenses with: <ul style="list-style-type: none"> — motorized focus, zoom, aperture, — electronically switchable infrared cut filter, — an adjustable focal length not less than 2,7 mm and not more than 55 mm, — a weight of not more than 100 g, — a length of less than 70 mm, — a diameter of not more than 60 mm 	0 %	-	31.12.2025
--------	---------------	----	--	-----	---	------------

(¹) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1):.